



Primer

FRA-A

Tables with vacuum unit

FEATURES

FRV-A (without boiler)

Vacuum ironing table + iron, with electrically heated board and suction.

Work table dimensions 1.200 x 400 x 250mm.

Adjustable temperature of the board by means of a thermostat.

Built-in single phase suction unit.

Works by means of a pedal.

Electric heated board.

Needs to be connected to an external steam supply.

Voltage: 230V I +N 50Hz.

FRA-A and FRA-A PLUS (with boiler both)

Vacuum ironing table + iron with suction and electrically heated board, controlled by a thermostat.

Work table dimensions 1.200 x 400 x 250mm.

Built-in electric steam boiler. Iron included. Second iron as option.

Automatic water feeding, automatic pressure control.

Feeding pump and emptying valve.

Works by means of a pedal.

Voltage: 400V III +N / 230V III / 230V I +N 50Hz.

FRA-A PLUS: Adjustable height of board from 750 to 950mm.



OPTIONS

- Sleeve arm for FR/A and FR/AS
- steam gun for FR/A and FR/AS
- Sliding trolley with light FR/A and FR/AVS
- Second iron (only models with boiler)

CAPACITY	UNIT.	FRA-A
		CON CALDERA
Boiler	-	YES
Boiler capacity	l	5
Board dimensions	mm	1.200 x 400 x 250
Adjustable height of board	-	NO
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	OPT
Sliding trolley with balancer and lighting	-	OPT
Second steam iron assembly	-	OPT
POWER		
Vacuum motor	kW	0,45
Pump motor	kW	-
Iron heater	kW	0,83
Board heater	kW	1
Boiler heater	kW	3,9
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	3/8"
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	2,8
Steam Consumption	kg/h	-
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	NI/min	-
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.550 / 1.520
Net depth / Gross depth	mm	580 / 580
Net height / Gross height	mm	950 / 1.140
Net weight / Gross weight	kg/h	87 / 103
Volume	m ³	0,85 / 1,01
OTHER		
Tension	V/Hz	230/400 V III 50
Sound level	dB	68

