



# Primer

FRA-A

## Tables with vacuum unit

### FEATURES

#### FRV-A (without boiler)

Vacuum ironing table + iron, with electrically heated board and suction.

Work table dimensions 1.200 x 400 x 250mm.

Adjustable temperature of the board by means of a thermostat.

Built-in single phase suction unit.

Works by means of a pedal.

Electric heated board.

Needs to be connected to an external steam supply.

Voltage: 230V I +N 50Hz.

#### FRA-A and FRA-A PLUS (with boiler both)

Vacuum ironing table + iron with suction and electrically heated board, controlled by a thermostat.

Work table dimensions 1.200 x 400 x 250mm.

Built-in electric steam boiler. Iron included. Second iron as option.

Automatic water feeding, automatic pressure control.

Feeding pump and emptying valve.

Works by means of a pedal.

Voltage: 400V III +N / 230V III / 230V I +N 50Hz.

**FRA-A PLUS:** Adjustable height of board from 750 to 950mm.



### OPTIONS

- Sleeve arm for FR/A and FR/AS
- steam gun for FR/A and FR/AS
- Sliding trolley with light FR/A and FR/AVS
- Second iron (only models with boiler)

| CAPACITY                                   | UNIT.  | FRA-A             |
|--|--------|-------------------|
|  |        | CON CALDERA       |
| Boiler                                     | -      | YES               |
| Boiler capacity                            | l      | 5                 |
| Board dimensions                           | mm     | 1.200 x 400 x 250 |
| Adjustable height of board                 | -      | NO                |
| OPTIONS                                    |        |                   |
| Swinging arm with heated sleeve shape      | -      | OPT               |
| Steam gun                                  | -      | OPT               |
| Sliding trolley with balancer and lighting | -      | OPT               |
| Second steam iron assembly                 | -      | OPT               |
| POWER                                      |        |                   |
| Vacuum motor                               | kW     | 0,45              |
| Pump motor                                 | kW     | -                 |
| Iron heater                                | kW     | 0,83              |
| Board heater                               | kW     | 1                 |
| Boiler heater                              | kW     | 3,9               |
| Sleeve-arm heater (option)                 | kW     | 0,09              |
| CONNECTIONS                                |        |                   |
| Ø Water inlet                              | BSP    | 3/8"              |
| Ø Boiler exhaust (with boiler)             | BSP    | 3/8"              |
| Ø Steam inlet                              | BSP    | -                 |
| Steam pressure                             | BAR    | 2,8               |
| Steam Consumption                          | kg/h   | -                 |
| Ø Air inlet                                | BSP    | -                 |
| Air pressure                               | BAR    | -                 |
| Air Consumption                            | NI/min | -                 |
| DIMENSIONS / PACKING DIMENSIONS            |        |                   |
| Net width / Gross width                    | mm     | 1.550 / 1.520     |
| Net depth / Gross depth                    | mm     | 580 / 580         |
| Net height / Gross height                  | mm     | 950 / 1.140       |
| Net weight / Gross weight                  | kg/h   | 87 / 103          |
| Volume                                     | m³     | 0,85 / 1,01       |
| OTHER                                      |        |                   |
| Tension                                    | V/Hz   | 230/400 V III 50  |
| Sound level                                | dB     | 68                |

