



Primer

FRA-AVS

Up-steaming, vacuum & blowing tables

FEATURES

FRV-AVS (sin caldera)

Vacuum, up-steaming and blowing ironing table + iron, with electrically heated board and suction.

- Work table dimensions 1.200 x 400 x 250mm.
- Blowing unit needs external supply of compressed air.
- Adjustable temperature of the board by means of a thermostat.
- Built-in single phase suction unit.
- Works by means of a pedal.
- Electric heated board.
- Needs to be connected to an external steam supply.
- Voltage: 230V I +N 50Hz.

FRA-AVS (con caldera)

Vacuum up-steaming and blowing ironing table + iron with suction and electrically heated board, controlled by a thermostat.

- Work table dimensions 1.200 x 400 x 250mm.
- Blowing unit needs external supply of compressed air.
- Built-in electric steam boiler. Iron included. Second iron as option.
- Automatic water feeding, automatic pressure control.
- Feeding pump and emptying valve.
- Works by means of a pedal.
- Electrical heating.
- Voltage: 400V III +N / 230V III.



OPTIONS

- Vacuum sleeve arm for MP-ASV/MP-ASV-C
- Steam gun for MP-ASV/MP-ASV-C
- Sliding trolley with light for MP-A/MPA-C/MP-AS/MP-AS-C/MP-AC PLUS
- Second iron (models with electric boiler only)

CAPACITY	UNIT.	FRA-AVS
		CON CALDERA
Boiler	-	YES
Boiler capacity	l	7
Board dimensions	mm	1.200 x 400 x 250
Adjustable height of board	-	NO
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	OPT
Sliding trolley with balancer and lighting	-	OPT
Second steam iron assembly	-	OPT
POWER		
Vacuum motor	kW	0,45
Pump motor	kW	0,75
Iron heater	kW	0,83
Board heater	kW	-
Boiler heater	kW	6-7,5
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	3/8"
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	4,5
Steam Consumption	kg/h	-
Ø Air inlet	BSP	1/4"
Air pressure	BAR	4-8
Air Consumption	NI/min	5
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.680 / 1.880
Net depth / Gross depth	mm	580 / 680
Net height / Gross height	mm	920 / 1.270
Net weight / Gross weight	kg/h	141 / 165
Volume	m ³	0,90 / 1,62
OTHER		
Tension	V/Hz	230/400V III
Sound level	dB	75

