



Primer

FRV-A

Tables with vacuum unit

FEATURES

FRV-A (without boiler)

Vacuum ironing table + iron, with electrically heated board and suction.

Work table dimensions 1.200 x 400 x 250mm.

Adjustable temperature of the board by means of a thermostat.

Built-in single phase suction unit.

Works by means of a pedal.

Electric heated board.

Needs to be connected to an external steam supply.

Voltage: 230V I +N 50Hz.

FRA-A and **FRA-A PLUS** (with boiler both)

Vacuum ironing table + iron with suction and electrically heated board, controlled by a thermostat.

Work table dimensions 1.200 x 400 x 250mm.

Built-in electric steam boiler. Iron included. Second iron as option.


Automatic water feeding, automatic pressure control.

Feeding pump and emptying valve.

Works by means of a pedal.

Voltage: 400V III +N / 230V III / 230V I +N 50Hz.

FRA-A PLUS: Adjustable height of board from 750 to 950mm.



OPTIONS

- Sleeve arm for FR/A and FR/AS
- steam gun for FR/A and FR/AS
- Sliding trolley with light FR/A and FR/AVS

CAPACITY	UNIT.	FRV-A
		SIN CALDERA
Boiler	-	NO
Boiler capacity	l	-
Board dimensions	mm	1.200 x 400 x 250
Adjustable height of board	-	NO
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	OPT
Sliding trolley with balancer and lighting	-	OPT
Second steam iron assembly	-	NO
POWER		
Vacuum motor	kW	0,45
Pump motor	kW	-
Iron heater	kW	0,83
Board heater	kW	1
Boiler heater	kW	-
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	-
Ø Boiler exhaust (with boiler)	BSP	-
Ø Steam inlet	BSP	1/4"
Steam pressure	BAR	-
Steam Consumption	kg/h	5
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	l/min	-
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.480 / 1.520
Net depth / Gross depth	mm	480 / 580
Net height / Gross height	mm	930 / 1.120
Net weight / Gross weight	kg/h	66 / 82
Volume	m³	0,66 / 0,98
OTHER		
Tension	V/Hz	230V 50
Sound level	dB	68

