



# Primer

FDA-A

## Tables with vacuum unit

### FEATURES

#### **FRV-A** (without boiler)

Vacuum ironing table + iron, with electrically heated board and suction.

Work table dimensions 1.200 x 400 x 250mm.

Adjustable temperature of the board by means of a thermostat.

Built-in single phase suction unit.

Works by means of a pedal.

Electric heated board.

Needs to be connected to an external steam supply.

Voltage: 230V I +N 50Hz.

#### **FRA-A** and **FRA-A PLUS** (with boiler both)

Vacuum ironing table + iron with suction and electrically heated board, controlled by a thermostat.

Work table dimensions 1.200 x 400 x 250mm.

Built-in electric steam boiler. Iron included. Second iron as option.

Automatic water feeding, automatic pressure control.

Feeding pump and emptying valve.

Works by means of a pedal.

Voltage: 400V III +N / 230V III / 230V I +N 50Hz.

**FRA-A PLUS:** Adjustable height of board from 750 to 950mm.



### OPTIONS

- Swinging arm with suction and heated sleeve shape

| CAPACITY                                   | UNIT.          | FDA-A             |
|--|----------------|-------------------|
|  |                | CON CALDERA       |
| Boiler                                     | -              | YES               |
| Boiler capacity                            | l              | 4                 |
| Board dimensions                           | mm             | 1.100 x 380 x 270 |
| Adjustable height of board                 | -              | NO                |
| OPTIONS                                    |                |                   |
| Swinging arm with heated sleeve shape      | -              | OPT               |
| Steam gun                                  | -              | NO                |
| Sliding trolley with balancer and lighting | -              | NO                |
| Second steam iron assembly                 | -              | NO                |
| POWER                                      |                |                   |
| Vacuum motor                               | kW             | 0,13              |
| Pump motor                                 | kW             | -                 |
| Iron heater                                | kW             | 0,8               |
| Board heater                               | kW             | 0,7               |
| Boiler heater                              | kW             | 1,45              |
| Sleeve-arm heater (option)                 | kW             | 0,09              |
| CONNECTIONS                                |                |                   |
| Ø Water inlet                              | BSP            | -                 |
| Ø Boiler exhaust (with boiler)             | BSP            | -                 |
| Ø Steam inlet                              | BSP            | -                 |
| Steam pressure                             | BAR            | 2,8               |
| Steam Consumption                          | kg/h           | -                 |
| Ø Air inlet                                | BSP            | -                 |
| Air pressure                               | BAR            | -                 |
| Air Consumption                            | NI/min         | -                 |
| DIMENSIONS / PACKING DIMENSIONS            |                |                   |
| Net width / Gross width                    | mm             | 1.380 / 1.300     |
| Net depth / Gross depth                    | mm             | 380 / 540         |
| Net height / Gross height                  | mm             | 930 / 1.160       |
| Net weight / Gross weight                  | kg/h           | 43 / 57           |
| Volume                                     | m <sup>3</sup> | 0,49 / 0,81       |
| OTHER                                      |                |                   |
| Tension                                    | V/Hz           | 230V   50         |
| Sound level                                | dB             | 70                |

