



Primer

S1000-3300 S Flatwork Ironers

FEATURES

Roll sizes: 2.600 and 3.300mm wide and 600, 800 and 1.000mm de diameter.

Panels in painted steel.

Frequency control.

Feeding and ironing belts are NOMEX.

Touch-screen control: programs can be created with speed control (between 3 and 18 mts/min) and temperature.

Automatic stop after cooling down (at 80°C).

Big output capacity, depending on the residual moisture of the linen, up to 290 kg/hour straight from the high spin washer extrator.

Electric, gas or steam heating.

Gas models with radiant burner (increase of 25% more production, available in diameter 800 models and standard in diameter 1.000 models).

Powerful exhaust system.



OPTIONS

- Vacuum table to help the linen feeding
- Automatic 1 lane clamp feeder without vacuum feeding belts
- Rear exit
- Motorized rear exit - height 860 mm. (rear exit included)
- Small pieces back collector: 2 lanes for S
- Small pieces back collector: 4 lanes for S
- Different voltage from 400V III +N 50 Hz
- Maritime packing for S

GENERAL DATA		UNIT.	S1000-3300
Theoretical production* elec/steam/atm. Gas heating		Kg/h	290
Theoretical production* radiant gas burner		Kg/h	331
Ø Roll		mm	1.000
Working width		mm	3.300
Height floor-feeding		mm	1.050
Working speed		mt/min	4-18
Control type		-	Digital
Nº of programs		Nº	20
POWER			
Electric heating		kW	90
Max. electric power electric heating		kW	92,6
Gas heating (natural / LPG)		kW	155,70 / 159,10
Max. electric power gas heating		kW	2,6
Steam heating		kW	150
Max. electric power steam heating		kW	2,6
CONNECTIONS			
Ø Gas inlet		BSP	1"
Ø Steam inlet (12 bar max.)		BSP	1-1/4"
Ø Condensed (steam models)		BSP	1"
Ø Air inlet		BSP	12
DIMENSIONS / PACKAGING DIMENSIONS			
Net width / gross width		mm	4.490 / 4.570
Net depth / gross depth		mm	2.090 / 2.280
Net height / gross height		mm	2.430 / 2.400
Net weight / gross weight		Kg	3.700 / 4.250
Volume		m3	22,80 / 25,01
OTHERS			
No. Fume outlet		Nº	2
Ø Fume outlet		mm	160
Extraction rate		m3/h	2 x 1.000
Compressed air consumption (6,5 bar)		mm	5.000
Sound Level		dB	70

* 50% residual moisture, 140gr/m² of cotton, 100% roll utilization

