



FEATURES

Steam generators GE-24

- Electric and automatic steam boiler SB-24 to supply steam to models without boiler. Available from 12 to 22 kW.
- Water feed can be connected directly to the water mains or to a condensate tank. Pressure between 1 and 7 bar.
 - Capacity 24,9 litres.
 - Voltage: 230/400V III 50-60Hz.

Small steam generators with iron FD-2

- Electric steam boiler with steam iron.
- Die-cast aluminium boiler, capacity 1,8 liters, heater 1 kW.
 - Manually operated water feeding (drinking water required for its functioning).
 - Automatic pressure control by thermostat with fixed setting.
 - Mobile trolley as option.
 - Voltage: 230V I +N 50-60Hz.

Small steam generators with iron FD-5

- Stainless steel electric steam boiler with electric steam iron.
- Boiler capacity 5 liters, heater 1,45 kW.
 - Water level indicator with warning light for empty boiler.
 - Three safety devices fitted on the boiler: pressure switch, safety valve and safety thermostat.
 - Manual water feed.
 - Mobile trolley as option.
 - Voltage: 230V I +N 50Hz.

Table with Hoover MD/5

- Folding ironing table with electrically heated board and built in suction unit.
- Without steam iron, without built-in boiler.
 - Board dimensions: 1.380 x 380 x 930 mm.



OPTIONS

- Wheels support

GENERAL DETAILS	UNIT.	FD-5
Boiler capacity	L	5,0
Steam pressure	Bar	-
Working temperature	°C	-
Working humidity	-	-
Boiler Heater	kW	1,45
Iron Heater	kW	0,80
Resistance table	W	-
Suction motor	W	-
POWER		
Boiler heaters	kW	-
Steam production	Kg/h	-
Pump motor power	HP	-
CONNECTIONS		
Water feeding inlet	in	-
Boiler exhaust	in	-
Steam inlet	in	-
Condensate return with valve	in	-
Autonomy	-	5/6
Operating pressure	BAR	2,8
DIMENSIONS		
Dimensions*	mm	262 x 397 x 1090
Height with wheel stand mounted (option)	mm	1580
Net weight	Kg	11
Gross weight	Kg	15
Packing dimensions	mm	600 x 450 x 540
Working dimensions	-	-
Voltage	V/Hz	230V 50
Sound level	dB	-

