



# Primer

## FRV-AS

## Tables with vacuum & blowing unit

### FEATURES

#### FRV-AS (without boiler)

Vacuum and blowing ironing table + iron, with electrically heated board and suction.

- Work table dimensions 1.200 x 400 x 270mm.
- Blowing unit needs external supply of compressed air.
- Adjustable temperature of the board by means of a thermostat.
- Built-in single phase suction unit.
- Works by means of a pedal.
- Electric heated board.
- Needs to be connected to an external steam supply.
- Voltage: 230V I +N 50Hz.

#### FRA-AS (with boiler)

Vacuum and blowing ironing table + iron with suction and electrically heated board and suction.

- Work table dimensions 1.200 x 400 x 270mm.
- Blowing unit needs external supply of compressed air.
- Adjustable temperature of the board by means of a thermostat.
- Built-in electric steam boiler. Iron included. Second iron as option.
- Automatic water feeding, automatic pressure control.
- Feeding pump and emptying valve.
- Works by means of a pedal.
- Electrical heating.
- Voltage: 400V III +N / 230V III or 230V I +N 50Hz.



### OPTIONS

- Vacuum sleeve arm for MP-A/MPA-C/MP-AS/MP-AS-C/MP-AC PLUS
- Steam gun for MP-A/MPA-C/MP-AS/MP-AS-C/MP-AC PLUS
- Sliding trolley with light for MP-ASV/MP-ASV-C

CAPACITY	UNIT.	FRV-AS
		SIN CALDERA
Boiler	-	NO
Boiler capacity	l	-
Board dimensions	mm	1.200 x 400 x 270
Adjustable height of board	-	YES
<b>OPTIONS</b>		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	OPT
Sliding trolley with balancer and lighting	-	OPT
Second steam iron assembly	-	NO
<b>POWER</b>		
Vacuum motor	kW	0,45
Pump motor	kW	-
Iron heater	kW	0,83
Board heater	kW	1
Boiler heater	kW	-
Sleeve-arm heater (option)	kW	0,09
<b>CONNECTIONS</b>		
Ø Water inlet	BSP	-
Ø Boiler exhaust (with boiler)	BSP	-
Ø Steam inlet	BSP	1/4"
Steam pressure	BAR	-
Steam Consumption	kg/h	5
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	NI/min	-
<b>DIMENSIONS / PACKING DIMENSIONS</b>		
Net width / Gross width	mm	1.500 / 1.520
Net depth / Gross depth	mm	600 / 580
Net height / Gross height	mm	1.800 / 1.120
Net weight / Gross weight	kg/h	81 / 97
Volume	m <sup>3</sup>	0,84 / 0,99
<b>OTHER</b>		
Tension	V/Hz	230V   50
Sound level	dB	70

