



Primer

MINI DES-F Spotting tables

FEATURES

DES-F

Cold spotting table with built-in suction unit and as option: in-built compressor.

- Featuring two cold spotting guns with independent circuits, two receptacles for liquids, hose support and swinging arm with suction.
- Satinless steel AISI 304 spotting shape.
- Plate dimensions: 800x260x175mm.
- Compressed air required: consumption 200 NI/min, pressure 4-8 bar.
- Electrical connection: 230V I +N / 50-60Hz.

MINI-DES

Compact cold spotting table.

- Equipped with two cold spotting guns with independent circuit and two tanks for solvents.
- One working pedal.
- Stainless steel AISI 304 board (400 x 200 x 35 mm).
- Electric connection: 230V I+N / 50-60Hz.
- It needs compressed air: consumption 30 NI/min, air working pressure 6-8 bar.



OPTIONS

- Trolley

GENERAL DETAILS	UNIT.	MINI DES-F
Board dimensions	mm	400 x 200 x 35
Boiler	-	NO
Compressor	-	-
Steam gun	-	-
POWER		
Vacuum motor	HP	0,13
Compressor motor (optional)	kW	-
CONNECTIONS		
Ø Steam inlet	BSP	-
Ø Condensate outlet	BSP	-
Steam pressure	BAR	-
Steam Consumption	Kg/h	-
Ø Air inlet	BSP	1/4"
Ø Air outlet	mm	-
Air pressure	BSP	6-8
Air Consumption	NI/min	30
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	640 / 600
Net depth / Gross depth	mm	320 / 450
Net height / Gross height	mm	325-670 / 540
Net weight / Gross weight	Kg	13 / 16
Volume	m ³	0,14 / 0,15
OTHERS		
Voltage	V/Hz	230V 50-60
Sound level	dB	65

