Primer

DL-14 P
BASIC dryers

P CONTROL

Push buttons to control temperature and time.

OUTSTANDING FEATURES

Reversing drum action as standard.
Galvanized drum as standard.
Frequency inverter as standard.

EFFICIENCY

Big fluff filter.

VERSATILITY

Make to order - customisation.
OPL > Multivending - Standard OPL model easily trasformable to coin laundry uses.

ERGONOMICS

Biggest door diameters.
Opening sense of door adjustable on site.

EASY MAINTENANCE

Hinged control panel: easy and ergonomic access.
Technical menu: statistics for technicians and maintenance with external console (with console option).
Easy to access to components.

OTHERS

White painted panels.
COOL DOWN - anti-wrinkle at the end of the cycle.
Heating options: electric or gas.
CE approved




OPTIONS

- Opposite door opening 11 to 35
- Back panel with air filter 11 to 35
- NG gas option (Natural) for DL
- Display for P programmer
- 400V 3N 60 Hz
- 230V 3~ 50 Hz DL-11/14/18 E
- 230V 3~ 60 Hz DL-11/14/18 E
- 230V 3~ 60 Hz DL-11 to 35 G/S
- 440/480 V III 60 Hz DL-11/14/18
- Reduced power (12kw instead of 18kw) for elect. heated DL-14/18
- Maritime wooden packing DL-14/18
- Several payment systems for self-service

CAPACITY & DRUM	UNIT.	DL-14 P	
Capacity 1/18	Kg	15	
	lb	33,1	
Capacity 1/20	Kg	13,5	
	lb	29,8	
Ø Drum	mm	750	
	inch	29,53	
Drum length	mm	610	
	inch	24,02	
Drum volume	l	270	
	cu ft	9,53	
Ø Door hole	mm	574	
	inch	22,60	
Door center height	mm	976	
	inch	38,4	
Height from floor to bottom of door	mm	618	
	inch	24,33	
ELECTRIC HEATING			
Evaporation capacity	L/h	13,5	
	US gallon/h	3,6	
Hourly output	Kg/h	26,9	
	lb/h	59,3	
Installed heating power	kW	18	
Installed electrical power	kW	18,67	
GAS HEATING			
Evaporation capacity (gas model)	L/h	15,4	
	US gallon/h	4,068	
Hourly output (gas model)	Kg/h	30,25	
	lb/h	66,7	
Installed gas heating power	kcal/h	17627	
	Btu/h	69996	
Installed gas heating power	kW	20,5	
Installed electrical power	kW	0,67	
Instant propane gas consumption (G31)	Kg/h	1,76	
	lb/h	3,88	
Instant natural gas consumption (G20)	m³/h	2,17	
	cfm	1,28	
Ø Gas inlet	BSPP ISO 228-1	1/2"	
POWER AND VENTILATION			
Drum motor power	kW	0,37	
Fan motor power	kW	0,25	
Nominal air flow rate	m³/h	850	
	cfm	500	
Ø Fume exhaust	mm	200	
Ø Fume exhaust	inch	7,87	
HEAT EMISSION			
Maximum total heat emission	kW	1,8	
	Btu/h	6145	
Max. front heat emission	kW	1,3	
	Btu/h	4302	
CONNECTIONS		E	G / S
Tension 230V - I + N + T	Nº x mm² / A	-	3 x 1,5 / 16A
Tension 230V - III + T	Nº x mm² / A	4 x 16 / 63A	3 x 1,5 / 16A
Tension 400V - III + N + T	Nº x mm² / A	5 x 10 / 32A	3 x 1,5 / 16A
NET DIMENSIONS / D. WITH PACKING			
Net / gross width	mm	785 / 865	
	inch	30,9 / 34,1	

Net / gross depth	mm	989 / 1.074
	inch	38,9 / 42,3
Net height / gross height without heating	mm	1.694 / 1.840
	inch	66,7 / 72,4
Net / gross weight	Kg	180 / 190
	lb	397 / 419
OTHERS		
Sound level	dB	64



01 POWER SUPPLY
02 FUMES OUTPUT Ø200
03 GAS INLET 1/2"
04 STEAM INLET 3/4"
05 CONDENSATE OUTLET 3/4"
06 ETHERNET CONNECTION (only available CONTROL T2 models)

* Measurement with legs mounted (30mm)

	A	B	C	D	D1	E	E1	F	G	H	I	J	K	L	M	N	O	P
DL - 11	1694*	1447	689	1354	1422	68	68	785	855	735	380	870	575	1226	133	180	35	805
DL - 14	1694*	1447	689	1354	1422	68	68	785	989	735	380	870	575	1226	133	180	35	805