



Primer

FRA-AS

Tables with vacuum & blowing unit

FEATURES

FRV-AS (without boiler)

Vacuum and blowing ironing table + iron, with electrically heated board and suction.

- Work table dimensions 1.200 x 400 x 270mm.
- Blowing unit needs external supply of compressed air.
- Adjustable temperature of the board by means of a thermostat.
- Built-in single phase suction unit.
- Works by means of a pedal.
- Electric heated board.
- Needs to be connected to an external steam supply.
- Voltage: 230V I +N 50Hz.

FRA-AS (with boiler)

Vacuum and blowing ironing table + iron with suction and electrically heated board and suction.

- Work table dimensions 1.200 x 400 x 270mm.
- Blowing unit needs external supply of compressed air.
- Adjustable temperature of the board by means of a thermostat.
- Built-in electric steam boiler. Iron included. Second iron as option.
- Automatic water feeding, automatic pressure control.
- Feeding pump and emptying valve.
- Works by means of a pedal.
- Electrical heating.
- Voltage: 400V III +N / 230V III or 230V I +N 50Hz.



OPTIONS

- Sleeve arm for FR/A and FR/AS
- steam gun for FR/A and FR/AS
- Sliding trolley with light FR/AS
- Second iron (only models with boiler)

CAPACITY	UNIT.	FRA-AS
		CON CALDERA
Boiler	-	YES
Boiler capacity	l	5
Board dimensions	mm	1.200 x 400 x 270
Adjustable height of board	-	YES
OPTIONS		
Swinging arm with heated sleeve shape	-	OPT
Steam gun	-	OPT
Sliding trolley with balancer and lighting	-	OPT
Second steam iron assembly	-	OPT
POWER		
Vacuum motor	kW	0,45
Pump motor	kW	-
Iron heater	kW	0,83
Board heater	kW	1
Boiler heater	kW	3,9
Sleeve-arm heater (option)	kW	0,09
CONNECTIONS		
Ø Water inlet	BSP	3/8"
Ø Boiler exhaust (with boiler)	BSP	3/8"
Ø Steam inlet	BSP	-
Steam pressure	BAR	2,8
Steam Consumption	kg/h	-
Ø Air inlet	BSP	-
Air pressure	BAR	-
Air Consumption	NI/min	-
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	1.500 / 1.520
Net depth / Gross depth	mm	600 / 580
Net height / Gross height	mm	1.800 / 1.120
Net weight / Gross weight	kg/h	100 / 116
Volume	m ³	1,62 / 0,99
OTHER		
Tension	V/Hz	230/400V III 50
Sound level	dB	70

