



Primer

S600-3300

S Flatwork Ironers

FEATURES

Roll sizes: 2.600 and 3.300mm wide and 600, 800 and 1.000mm de diameter.

Panels in painted steel.

Frequency control.

Feeding and ironing belts are NOMEX.

Touch-screen control: programs can be created with speed control (between 3 and 18 mts/min) and temperature.

Automatic stop after cooling down (at 80°C).

Big output capacity, depending on the residual moisture of the linen, up to 290 kg/hour straight from the high spin washer extrator.

Electric, gas or steam heating.

Gas models with radiant burner (increase of 25% more production, available in diameter 800 models and standard in diameter 1.000 models).

Powerful exhaust system.




OPTIONS

- Vacuum table to help the linen feeding
- Automatic 1 lane clamp feeder without vacuum feeding belts
- Rear exit
- Motorized rear exit - height 860 mm. (rear exit included)
- Small pieces back collector: 2 lanes for S
- Small pieces back collector: 4 lanes for S
- Different voltage from 400V III +N 50 Hz
- Maritime packing for S

GENERAL DATA		UNIT.	S600-3300
Theoretical production* elec/steam/atm. Gas heating		Kg/h	160
Theoretical production* radiant gas burner		Kg/h	-
Ø Roll		mm	600
Working width		mm	3.300
Height floor-feeding		mm	1.050
Working speed		mt/min	3-10
Control type		-	Digital
Nº of programs		Nº	20
POWER			
Electric heating		kW	54
Max. electric power electric heating		kW	55,9
Gas heating (natural / LPG)		kW	80,30 / 86,30
Max. electric power gas heating		kW	1,9
Steam heating		kW	75
Max. electric power steam heating		kW	1,9
CONNECTIONS			
Ø Gas inlet		BSP	1"
Ø Steam inlet (12 bar max.)		BSP	1"
Ø Condensed (steam models)		BSP	1/2"
Ø Air inlet		BSP	12
DIMENSIONS / PACKAGING DIMENSIONS			
Net width / gross width		mm	4.370 / 4.530
Net depth / gross depth		mm	1.440 / 1.620
Net height / gross height		mm	2.030 / 1.960
Net weight / gross weight		Kg	2.050 / 2.350
Volume		m3	12,77 / 14,38
OTHERS			
No. Fume outlet		Nº	2
Ø Fume outlet		mm	120
Extraction rate		m3/h	2 x 1.000
Compressed air consumption (6,5 bar)		mm	5.000
Sound Level		dB	70

* 50% residual moisture, 140gr/m² of cotton, 100% roll utilization



	H	I	T	S	A	C	E	F	G	V
S600-2600	1.800	3.242	186	152	Ø 12	1/2"	5 x 2,5	Ø 120	1"	1"
S600-3300	1.800	3.942	186	152	Ø 12	1/2"	5 x 2,5	Ø 120	1"	1"