



# Primer

## SPE1000-1-2600 SPE Flatwork Ironers

### FEATURES

Flatwork ironer with roll sizes: 2.600 and 3.300mm long and diameter 600, 800 and 1.000mm.

Panels in painted steel.

One or two working lanes: one lane for bedsheets and two lanes for tablecloth and smaller pieces.

Length fold (1 or 2 folds) and crossfold (up to 3 folds).

Folding system by photocells and compressed air.

Two types of linen stacker, with possibility to program the number of items stacked. The stacker can be positioned on either side of the machine.

Frequency control.

Feeding and ironing belts are NOMEX.

Touch-screen control: programs can be created with speed control (between 3 and 18mts/min), temperature and folding parameters.

Automatic stop after cooling down (at 80°C).

Big output capacity, depending on the residual moisture of the linen, up to 290kg/hour directly from the high spin washer extractor.

Electric, gas or steam heating.

Efficient gas models with radiant burner (increase of 25% more production, available in diameter 800 models and standard in diameter 1.000 models).

Powerful exhaust system.





### OPTIONS

- Four lanes for lengthfolding
- Motorized high table for side exit (no stacker) H=805mm
- Low table for side exit (no stacker) H=480mm
- Rotating control panel
- Stacker - it can stack up to 10 - 15 tablecloth, 10 bedsheets
- Compact (roll-off) stacker - it can stack up to 5 tablecloth
- Vacuum feeding belts to help the linen feeding
- Automatic 1 lane clamp feeder without vacuum feeding belts
- By pass for rear exit or to adapt Smarty
- Rear exit with table + bypass
- Small pieces back collector: 2 lanes + bypass included
- Small pieces back collector: 4 lanes + bypass included
- Double air pressure in length folds for thicker linen
- Linen reject system (dirty or torn)
- Remote service
- Different voltage from 400V III +N 50 Hz
- Maintenance Kit for Ironers
- Maritime packaging SPE
- Maritime packing for side stacker
- Maritime packing for ROLL OFF
- Maritime packing for small pieces collector 2 lanes
- Maritime packing for small pieces collector 4 lanes

GENERAL DATA		UNIT.	SPE1000-1-2600
Theoretical production* elec/steam/atm. Gas heating		Kg/h	190-230*
Ø Roll		mm	1.000
Working width		mm	2.600
Height floor-feeding		mm	1.050
Working speed		mt/min	4-18
Control type		-	Digital
Nº of programs		Nº	20
Side stacker		Nº	Opt.
FOLDING			
1 lane - lengthfold		Nº	1-2
1 lane - crossfold		Nº	1-2-3
2 lanes - lengthfold		Nº	1-2
2 lanes - crossfold		Nº	1-2
POWER			
Electric heating		kW	90
Max. electric power electric heating		kW	93,4
Gas heating (natural / LPG)		kW	120,90 / 121,30
Max. electric power gas heating		kW	3,9
Steam heating		kW	120
Max. electric power steam heating		kW	3,9
CONNECTIONS			
Ø Gas inlet		BSP	1"
Ø Steam inlet (12 bar max.)		BSP	1-1/4"
Ø Condensed (steam models)		BSP	1"
Ø Air inlet		BSP	12
DIMENSIONS / PACKAGING DIMENSIONS			
Net width / gross width		mm	3.740 / 3.900
Net depth / gross depth		mm	2.290 / 2.300
Net height / gross height		mm	2.480 / 2.290
Net weight / gross weight		Kg	3.960 / 4.410
Volume		m3	21,24 / 20,54
OTHERS			
No. Fume outlet		Nº	2
Ø Fume outlet		mm	160
Extraction rate		m3/h	2 x 1.000
Compressed air consumption (6,5 bar)		mm	21.000
Sound Level		dB	70

\* 50% residual moisture, 140gr/m<sup>2</sup> of cotton, 100% roll utilization





- A. Compressed air inlet
- C. Condensation discharge (steam models)
- E. Electrical connection
- F. Fumes extraction
- G. Gas inlet
- V. Steam inlet

Compact Stacker

	L	P
SPE1000-2600	4.425	2.385
SPE1000-3300	5.125	2.385

Stacker

	L	P
SPE1000-2600	5.105	2.476
SPE1000-3300	5.805	2.476

	H	I	T	S	A	C	E	F	G	V	W
SPE1000-2600	2.247	1.196	1.208	345	Ø 12	1"	5G4	Ø 160	1"	1-1/4"	800
SPE1000-3300	2.247	1.896	1.208	345	Ø 12	1"	5G4	Ø 160	1"	1-1/4"	800