



P CONTROL

Push buttons to control temperature and time.

OUTSTANDING FEATURES

Reversing drum action as standard.
Galvanized drum as standard.
Frequency inverter as standard.

EFFICIENCY

Big fluff filter.

VERSATILITY

Make to order - customisation.
OPL > Multivending - Standard OPL model easily transformable to coin laundry uses.

ERGONOMICS


Biggest door diameters.
Opening sense of door adjustable on site.

EASY MAINTENANCE

Hinged control panel: easy and ergonomic access.
Technical menu: statistics for technicians and maintenance with external console (with console option).
Easy to access to components.

OTHERS

White painted panels.
COOL DOWN - anti-wrinkle at the end of the cycle.
Heating options: electric or gas.
CE approved




OPTIONS

- Opposite door opening 11 to 35
- Back panel with air filter 11 to 35
- NG gas option (Natural) for DL
- Display for P programmer
- 400 V III N 60 Hz
- 230 V III 50 Hz DL-22/28/35
- 230 V III 60 Hz DL-22/28/35
- 230 V III 60 Hz DL-11 to 35 G/S
- 440/480 V III 60 Hz DL-22/28/35
- Maritime wooden packing DL-22
- Several payment systems for self-service

CAPACITY & DRUM		UNIT.	DL-22 P	
Capacity 1/18		Kg	24,4	
		lb	53,9	
Capacity 1/20		Kg	22,0	
		lb	48,5	
Ø Drum		mm	835	
		inch	32,87	
Drum length		mm	800	
		inch	31,5	
Drum volume		l	440	
		cu ft	15,54	
Ø Door hole		mm	574	
		inch	22,60	
Door center height		mm	1.030	
		inch	40,55	
Height from floor to bottom of door		mm	672	
		inch	26,46	
ELECTRIC HEATING				
Evaporation capacity		L/h	17	
		US gallon/h	4,5	
Hourly output		Kg/h	34	
		lb/h	75	
Installed heating power		kW	24	
Installed electrical power		kW	24,97	
GAS HEATING				
Evaporation capacity (gas model)		L/h	20	
		US gallon/h	5,283	
Hourly output (gas model)		Kg/h	40	
		lb/h	88,2	
Installed gas heating power		kcal/h	26655	
		Btu/h	105776	
Installed gas heating power		kW	31	
Installed electrical power		kW	0,97	
Instant propane gas consumption (G31)		Kg/h	2,66	
		lb/h	5,86	
Instant natural gas consumption (G20)		m ³ /h	3,28	
		cfm	1,93	
Ø Gas inlet		BSPP ISO 228-1	1/2"	
POWER AND VENTILATION				
Drum motor power		kW	0,37	
Fan motor power		kW	0,55	
Nominal air flow rate		m ³ /h	1.200	
		cfm	706	
Ø Fume exhaust		mm	200	
Ø Fume exhaust		inch	7,87	
HEAT EMISSION				
Maximum total heat emission		kW	2,4	
		Btu/h	8194	
Max. front heat emission		kW	1,7	
		Btu/h	5736	
CONNECTIONS			E	G / S
Tension 230V - I + N + T		Nº x mm ² / A	-	3 x 1,5 / 16A
Tension 230V - III + T		Nº x mm ² / A	4 x 25 / 80A	3 x 1,5 / 16A
Tension 400V - III + N + T		Nº x mm ² / A	5 x 10 / 40A	3 x 1,5 / 16A
NET DIMENSIONS / D. WITH PACKING				
Net / gross width		mm	890 / 970	
		inch	35 / 38,2	



Net / gross depth	mm	1.255 / 1.345
	inch	49,4 / 53
Net height / gross height without heating	mm	1.812 / 1.940
	inch	71,3 / 76,4
Net / gross weight	Kg	210 / 230
	lb	463 / 507
OTHERS		
Sound level	dB	65



- 01 POWER SUPPLY
- 02 FUMES OUTPUT Ø200
- 03 GAS INLET 1/2"
- 04 STEAM INLET 3/4" (DL-18)
- 05 STEAM INLET 1" (DL-22)
- 06 CONDENSATE OUTLET 3/4" (DL-18)
- 07 CONDENSATE OUTLET 1" (DL-22)
- 08 ETHERNET CONNECTION (only available CONTROL T2 models)

* Measurement with legs mounted (30mm)

	A	B	C	D	D1	E	E1	F	G	H	I	J	K	L	M	N	O	P
DL - 18	1694*	1447	689	1354	1422	68	68	785	1125	735	380	870	575	1226	133	180	35	805
DL - 22	1812*	1552	743	1430	1532	112	55	890	1255	735	107	920	575	1344	238	180	37	860

